

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Product number 840

Product name Stainless Steel Polish & Cleaner

Effective date 10-Dec-2008

Company information Claire Manufacturing

500 Vista Ave.

Addison, IL 60101 United States

Company phone General Assistance 630-543-7600

Emergency telephone US 800-424-9300 Emergency telephone outside US 703-527-3887

Version # 05

Supersedes date 05-Nov-2007

2. Hazards Identification

Emergency overview CONTENTS UNDER PRESSURE. Aerosol. Pressurized container may explode when

exposed to heat or flame.

Harmful in contact with eyes. Prolonged exposure may cause chronic effects.

FLAMMABLE

Potential health effects

Routes of exposure Ingestion. Skin contact. Eye contact.

Eyes Contact may irritate or burn eyes. Eye contact may result in corneal injury.

Skin Prolonged or repeated contact can result in defatting and drying of the skin which may

result in skin irritation and dermatitis (rash).

Inhalation Intentional misuse by concentrating and inhaling the product can be harmful or fatal.

Prolonged inhalation may be harmful.

Ingestion Exposure by ingestion of an aerosol is unlikely. May cause delayed lung damage.

Components of the product may be absorbed into the body by ingestion.

Target organs Central nervous system. Lungs.

Chronic effects Conjunctiva. May cause central nervous system disorder (e.g., narcosis involving a loss

of coordination, weakness, fatigue, mental confusion, and blurred vision) and/or damage.

May cause delayed lung damage.

3. Composition / Information on Ingredients

Components	CAS#	Percent
Synthetic Isoparaffinic Hydrocarbon	64742-47-8	20 - 30
Propane	74-98-6	10 - 15
Odorless Mineral Spirits	64742-48-9	10 - 15
Acetone	67-64-1	10 - 15
Methyl Acetate	79-20-9	8 - 10
Non-hazardous and other components below reportable levels		20 - 40

4. First Aid Measures

First aid procedures

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact

lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.

Skin contact Immediately take off all contaminated clothing. Wash off with warm water and soap. Get

medical attention if irritation develops or persists.

Inhalation Move to fresh air. If symptoms persist, get medical attention.

If material is ingested, immediately contact a poison control center. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

5. Fire Fighting Measures

Flammable properties

Containers may explode when heated. Vapor or gas may spread to distant ignition sources and flash back. Runoff to sewer may cause fire or explosion hazard.

Extinguishing media

Suitable extinguishing media

Protection of firefighters

Specific hazards arising from the chemical

Protective equipment and precautions for firefighters

Water fog. Alcohol foam. Dry chemical. Carbon dioxide (CO2).

Fire may produce irritating, corrosive and/or toxic gases.

In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.

6. Accidental Release Measures

Methods for containment

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Stop the flow of material, if this is without risk. Prevent entry into waterways, sewers, basements or confined areas.

Methods for cleaning up

Should not be released into the environment. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.

7. Handling and Storage

Handling

Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Use only in area provided with appropriate exhaust ventilation. Do not use if spray button is missing or defective. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.

Storage

Level 3 Aerosol.

Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Keep away from heat, sparks, and flame. Avoid exposure to long periods of sunlight. Store in cool place. Keep in an area equipped with sprinklers. Keep out of the reach of children. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit.

8. Exposure Controls / Personal Protection

Exposure limits

Components	CAS#	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	500 ppm	750 ppm	Not established
Methyl Acetate	79-20-9	200 ppm	250 ppm	Not established
OSHA				

JSHA

Components	CAS#	TWA	STEL	Ceiling
Propane	74-98-6	1000 ppm	Not established	Not established
Acetone	67-64-1	1000 ppm	Not established	Not established
Methyl Acetate	79-20-9	200 ppm	Not established	Not established

Personal protective equipment

Eye / face protection Wear chemical goggles.

Skin protection Wear appropriate chemical resistant clothing. Protective gloves.

Respiratory protectionWhen workers are facing concentrations above the exposure limit they must use appropriate certified respirators. If permissible levels are exceeded use NIOSH

mechanical filter / organic vapor cartridge or an air-supplied respirator.

9. Physical & Chemical Properties

Appearance Not available

Boiling point 320 °F (160 °C) estimated

Color Colorless.

Flammability (HOC) 34.7504 kJ/g estimated

Flash back No

Flash point -156 °F (-104.4 °C) estimated

Form Aerosol.

Odor solvent fruity

pH Not Applicable

Physical state Liquid.

Pressure 40 - 60 psig @ 70F

Solubility Negligible
Specific gravity 0.7474 estimated

10. Chemical Stability & Reactivity Information

Chemical stability Risk of ignition.

Conditions to avoid Heat, flames and sparks.

Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological Information

Acute effectsAcute LC50: 24 mg/l/4h estimated, Rat, InhalationSensitizationNot expected to be hazardous by OSHA criteria.Reproductive effectsNot expected to be hazardous by OSHA criteria.TeratogenicityNot expected to be hazardous by OSHA criteria.

12. Ecological Information

Ecotoxicity Components of this product have been identified as having potential environmental

concerns.

LC50 199 mg/L estimated, Fish, 96.00 Hours, EC50 9949 mg/L estimated, Daphnia, 48.00 Hours, IC50 1294 mg/L estimated, Algae, 72.00 Hours,

13. Disposal Considerations

Waste codes D001: Waste Flammable material with a flash point <140 F

Disposal instructionsContents under pressure. Do not puncture, incinerate or crush. Dispose of this material and its container at hazardous or special waste collection point. Do not allow this material

to drain into sewers/water supplies. If discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.

14. Transport Information

Department of Transportation (DOT) Requirements

Basic shipping requirements:

Proper shipping name Consumer commodity

Hazard class ORM-D Subsidiary hazard class None

Additional information:

Packaging exceptions 156, 306
Packaging non bulk 156, 306
Packaging bulk None

IMDG

Basic shipping requirements:

Proper shipping name AEROSOLS

Hazard class2.1UN number1950

Additional information:

Packaging exceptionsLTD QTYItem5FLabels requiredNoneTransport Category2



Basic shipping requirements:

Proper shipping name Aerosols, flammable

Hazard class2.1UN number1950

Additional information:

Packaging exceptions LTD QTY
Labels required 2.1





15. Regulatory Information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous

chemical

Yes

CERCLA (Superfund) reportable quantity

Acetone: 5000.0000

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - Yes Reactivity Hazard - No

Section 302 extremely No

hazardous substance

Section 311 hazardous chemical Yes

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of New and Existing Chemicals (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

State regulations

U.S. - Pennsylvania - RTK (Right to Know) List

Acetone 67-64-1 Environmental hazard

Methyl Acetate 79-20-9 Present Propane 74-98-6 Present

16. Other Information

Further information HMIS® is a registered trade and service mark of the NPCA.

HMIS® ratings Health: 2*

Flammability: 4 Physical hazard: 0 Personal protection: X

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our

knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified

in the text.

MSDS sections updated This document has undergone significant changes and should be reviewed in its entirety.