MATERIAL SAFETY DATA SHEET

Page: 1 of 4

2/17/09

Company Name Address:

Information Telephone Number(s)

Pro-Link Inc,

500 Chapman St., Canton, MA 02021

781-828-9550

Section 1 - Product Information

Product Name (ID #):

40% OMU Finish

EMERGENCY TELEPHONE NUMBER

Product Type:

Oil Modified Urethane

1-800-535-5053

Section 2 - Information on Ingredients

Chemical Name

% by Weight

Cas#

OSHA PEL

ACGIH TLV

Mineral Spirits

< 60%

8052-41-3

100 ppm

100ppm (TWA)



*Chemicals marked with an asterick in Section Two are subject to the reporting requirements for Section 313 of Tille III of the Superfund Amendments & Reauthorization Act (SARA) of 1986 & 40 CFR Part 372.

Section 3 - Hazards Identification

Emergency Overview:

Keep Out of Reach of Children. Warning, Combustible. Causes eye and skin irritation. Harmful or Fatal if swallowed.

Potential Health Effects

Primary Routes of Exposures

Eyes, skin, oral and inhalation are the principal routes of exposure.

Acute Eye Contact:

May cause mild eye irritation.

Acute Skin Contact:

Can cause irritation to skin on contact.

Acute Ingestion:

Ingestion of excessive quantities may cause irritation to the digestive tract.

Acute Inhalation:

Breathing high concentrations of vapors may cause irritation to the nose, throat and signs of nervous system depression (i.e. headache, dizziness, etc.).

Chronic Information:

Unknown

Carcinogenicity:

IARC - No

NTP - No

OSHA - No

ACGIH - No

Page: 2 of 4

Section 4 - First Aid Measures

Skin Contact:

Flush with water for 15 minutes while removing contaminated clothing and shoes. If symptoms persists, get medical attention.

Eye Contact:

Flush eyes with water for 15 minutes while holding eyelids open. Seek medical attention if irritation persists.

Ingestion:

DO NOT induce vomiting or give anything by mouth as possibility of product reaching the lung and causing damage.

Inhalation:

Remove to fresh air. If qualified give oxygen or artificial respiration as necessary and seek medical help.

(If any condition persists - Consult a physician).

Section 5 - Fire Fighting Measures

Flash Point (Method): 105°F (T.C.C.)

Flammable Limits: LFL NE

UFL: NE

2/17/09

Fire & Explosion Hazards: No unusual hazards.

Extinguishing Media:

Dry chemical, foam or carbon dioxide.

Special Fire Fighting Procedures:

Use water spray to cool fire exposed containers. Wear self-contained breathing apparatus.

Hazardous Combustion Products:

Oxides of carbon.

Section 6 - Accidental Release Measures

Dike area to contain spill. Absorb into appropriate absorbent material.

Section 7 - Handling and Storage

Store in well ventilated, cool area in tightly closed containers. Keep out of reach of children.

Section 8 - Exposure Controls Personal Protection

Eye Protection:

Safety Glasses or Goggles

Skin Protection:

Rubber Gloves

Respiratory Protection:

If concentration exceeds exposure limit, use NIOSH approved respirator for organic vapors.

Ventilation Requirements:

Local and mechanical exhausts to keep below any listed TLV.

Other:

Impervious clothing to avoid direct skin contact.

Section 9 - Physical / Chemical Properties

Physical Form: Liquid pH: NA

Color: Clear Amber Specific Gravity: 0.88

Odor: Solvent Solubility: Insoluble

Boiling Point: > 280°F Freezing Point: NE

Evaporation Rate: Faster than water % Volatile: 60%

Vapor Pressure: NE V.O.C. 448 gm/l

Section 10 - Stability and Reactivity

Stability:

This product is stable at ambient temperature and pressure.

Hazardous Decomposition Products:

Carbon Monoxide and/or Carbon Dioxide.

Hazardous Polymerization:

Will not occur.

Incompatibility:

Strong oxidizers and reducing agents.

2/17/09

Section 11 - Toxicology Information

Not established.

Section 12 - Ecology Information

Not established.

Section 13 - Disposal Considerations

Place in a D.O.T. approved drum. Check all Federal, State and Local regulations.

Section 14 - Transport Information

DOT

Proper Shipping Name: Combustible liquid, N.O.S. (Aliphatic and Aromatic Hydrocarbons), Combustible liquid

Packing Group:

Emergency Guide No: 128

DOT Label:

Combustible

Hazard Class: 3

ID Number: NA 1993

Section 15 - Regulatory Information

Toxic Substances Control Act:

All components of this product are on the TSCA inventory.

Section 311 / 312:

Immediate, delayed health hazard, fire hazard.

Section 313:

See section 2.

OSHA Hazard Communications Standard (29 CFR 1910.1200)

This product is hazardous by definition of the Hazard Communication Standard.

NPCA Hazardous Material Identification System (HMIS Rating) Health 2

Flammability 2

Reactivity 0

Section 16 - Other Information

Disclaimer: No representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose or of any other nature, are made with respect to information concerning the product referred to in this document. The information contained herein is, to the best of our knowledge and belief, accurate. However, it is impossible to foresee every health effect or exposure risk incurred by the use of this product. All chemicals present unknown health hazards and should always be used with caution. The information and recommendations contained herein are presented in good faith and are supplied pursuant to 29 CFR 1910.1200. The user should review this information in conjunction with their knowledge of the application intended to determine the suitability of this product for such purpose. In no event will the supplier be responsible for any damages of any nature whatsoever, with all applicable Federal, State and local regulations governing the use and disposal of this material.

Prepared by: Regulatory Affairs Department.